
ZEROING

Final zeroing of your firearm and scope should be done with live ammunition and based on your expected shooting distance. If you anticipate most of your shooting at short range, zero-in at 50 yards. Groups of three shots will be useful for averaging the point of impact.

ELEVATION & WINDAGE


Elevation or windage adjustments are made by removing the cover caps from the adjustment knobs. Using a screwdriver or coin, make adjustments in the appropriation of the state of the stat ate "UP" and/or "R" direction indicated by the arrows. Each "click" or stop in the adjustment will change the bullet impact by 1 Minute Of Angle (MOA) which translates to 1/2 inch at 50 yds., 1 inch at 100 yds., and 2 inches at 200 yds. Reinstall the cover caps over the adjustments to protect your zero and to exclude dirt from the mechanism.



BATTERY

Your Illuminated Red Dot Scope is powered by a long life 3V lithium battery, type 2032. If you ever have to change your battery, grasp the battery cover and turn counter clockwise until the battery is exposed. With a small screw driver or similar object, gently pry the battery free. Install the replacement battery by firmly pushing it into the battery cavity. The positive (+) side must face towards you. Replace the battery cover and tighten.


CAUTION: BE SURE GUN IS NOT LOADED WHEN INSTALLING THE BATTERY



ENGLISH

Congratulations on selecting your new Bushnell Illuminated Red Dot Scope. This scope has been specifically designed for use on shotguns, rifles and handguns. It is constructed and assembled by highly skilled craftsmen to Bushnell's high quality standards. The precision and craftsmanship with which this scope was built ensures its performance under demanding conditions. This scope will provide the shooting accuracy and repeatability which have made Bushnell legendary.

The following photographs are a guide to the nomenclature and location of the parts mentioned throughout this text.



NOTE: POSITION OF CONTROLS AND NUMBER OF EXTENSION TUBES MAY VARY BY MODEL.

This scope has a magnification of one power (1x). Therefore, no focusing is required. The clarity and resolutions will be as sharp and defined as can be seen with your eyes.

MOUNTING

The base and rings (mount) can affect your shotgun, rifle or handgun shooting performance and accuracy. If your scope is mounted improperly, you may never achieve the best accuracy from your firearm. You may choose to mount your own scope or opt to have a gunsmith do it for you.

Your scope should be mounted as low on the firearm as possible. This will keep your face or cheek close to the line of sight and will also keep the scope close to the

LIFETIME LIMITED WARRANTY

Your Bushnell® product is warranted to be free of defects in materials and workmanship for the lifetime of the original owner. The Lifetime Limited Warranty is an expression of our confidence in the materials and mechanical workmanship of our products and is your assurance of a lifetime of dependable service. In the event of a defect under this warranty, we will, at our option, repair or replace the product, provided that you return the product postage prepaid. This warranty does not cover damages caused by misuse, improper handling, installation, or maintenance provided by someone other than a Bushnell Authorized Service Department.

Any return in the U.S. or Canada made under this warranty must be accompanied by the items listed below:

- A check/money order in the amount of \$10.00 to cover the cost of postage and handling
 Name and address for product return
- An explanation of the defect
- Proof of Purchase
- 5) Product should be well packed in a sturdy outside shipping carton, to prevent damage in transit, with return postage prepaid to the address listed below:

IN U.S.A. Send To: Bushnell Outdoor Products Attn.: Repairs 8500 Marshall Drive Lenexa, Kansas 66214

IN CANADA Send To: Bushnell Outdoor Products Attn.: Repairs 25A East Pearce Street, Unit 1 Richmond Hill, Ontario L4B 2M9

For products purchased outside the United States or Canada please contact your local dealer for applicable warranty information. In Europe you may also contact Bushnell at: BUSHNELL Performance Optics Gmbh

European Service Centre MORSESTRASSE 4 D- 50769 KÖLN GERMANY Tél: +49 (0) 221 709 939 3 Fax: +49 (0) 221 709 939 8

> This warranty gives you specific legal rights. You may have other rights which vary from country to country.
>
> ©2006 Bushnell Outdoor Products